



HCTC, UAB
Pramonės g.97
LT-11115, Vilnius
Lithuania
2009

EN 14351-1: 2006+A1:2010

Facade Door

IV 68 wooden outside entrance doors from glued timber
For commercial and private buildings

Resistance against wind load	C3
Water tightness	4A
Bearing capacity of safety devices	npd
Sound insulation	34(0;-3) dB
Thermal transmission coefficient	1.5*
Air permeability	4
Resistance to repeated opening and closing	3
Mechanic durability	3
Dangerous substances	none

npd - no performance determined;

* - where detailed calculation of the heat from a specific building is required, the manufacturer shall provide accurate and relevant, calculated or tested thermal transmittance values (design values).

EC-Declaration of Conformity

HCTC, UAB
Pramonės g.97
LT-11115, Vilnius
Lithuania
2009

Declares, that the product **IV 68** wooden outside entrance doors from glued timber
for privately and commercially used buildings
is conform with

- the product features which are declared on the CE-mark according to

EN 14351-1:2006+A1:2010 appendix ZA

Initial tests were done by the following notified body:

Institute of Architecture and Construction of Kaunas University of Technology,
Laboratory of Building Thermal Physics, Tunelio g. 60, LT-44405, Kaunas,
Lithuania

Date:

Signature: